

HD1800 – DUAL BOOM HEDGER
SPECIFICATION SHEET

SPECIFICATIONS

- ❑ ONE PATH HEDGING (BOTH SIDES).....16'3" (495 CM)
- ❑ MINIMUM HEDGING WIDTH.....4'11" (150 CM)
- ❑ MAXIMUM HEDGING WIDTH.....12' (365 CM)
- ❑ MAXIMUM HEDGING HEIGHT (AT 4'11' HEDGING WIDTH).....22'9" (695 CM)
- ❑ HEDGING ANGLES.....FROM VERTICAL POSITION 5⁰ INWARD, 25⁰ OUTWARD
- ❑ TRANSPORT HEIGHT (WITH BLADES INSTALLED).....12'1" (370 CM)
- ❑ MACHINE WEIGHT.....21,800 LBS (9900 KG)
- ❑ SAW BLADES.....8 - 24" DIAMETER, PROPRIETARY SAW BLADES

SELF PROPELLED POWER UNIT:

Includes the following components:

- ❑ ITL heavy duty front and rear axles
- ❑ JOHN DEERE 6068T Tier 3, 155 HP (at 2500 RPM), turbo charged diesel engine
- ❑ JOHN DEERE / FUNK pump drive
- ❑ JOHN DEERE / FUNK 2-speed transmission
 - ❑ Operation mode: 0 – 5 MPH
 - ❑ Transport mode: 0 – 12 MPH
- ❑ EATON hydrostatic drive system
- ❑ Heavy Duty front and rear rims and tires
 - ❑ Rear tires 16.9 x 34 – 18 ply forestry tire
 - ❑ Front tires 14.9 x 24 – 18 ply forestry tire

HYDRAULIC SYSTEM

- ❑ Saw blade rotation circuit – **COMMERCIAL** gear type pump.
- ❑ Arm rotation circuit – **EATON** variable displacement piston pump with 2000 series
- ❑ **CHARLYNN** motor.
- ❑ Control circuit – gear type pump operating:
 - ❑ Cutting arm height cylinder
 - ❑ Cutting arm width cylinder
 - ❑ Cutting arm angle cylinder
- ❑ Hydrostatic drive circuit – **EATON** pump and motor.
- ❑ Cooling package fan circuit – gear type pump.

OPERATOR CAB:

The large, heavy duty, flat-deck operator’s cab is mounted as a separate unit on rubber mounts to reduce noise, vibration and heat. Pressure gauges mounted on the control panel allow the operator to continually monitor the machine load. The front windows of the cab are made of tempered glass providing unobstructed vision and safety. The side windows are covered with laser cut metal screen for ventilation (Air conditioned cabs include tempered glass on the side windows).

COOLING SYSTEM :

A self-cleaning cooling system mounted at the rear of the machine contains three radiators for the following:

- Engine coolant
- Hydraulic oil
- Air conditioning condenser

A maintenance free, automatic dust vacuum system removes and discharges debris before it gets to the radiators, to ensure constant operation under normal working temperature.

SAFETY:

In the design, components selection, and manufacturing, as well as in the servicing and operating instructions, much thought has been given to providing a machine with high productivity, low maintenance, long life, and above all operator safety.

LITERATURE:

Each unit is supplied with full documentation for all systems. This includes a “General Safety and Operations Manual” and “Specifications and Spare Parts Manual”.

FINISH:

- Machine parts are sand blasted, primed and painted.
- Machine bolts are zinc plated, grade 5.
- Saw blade propelling and rotation parts (pulleys, shafts, washers, etc.) are zinc plated.
- The machine is assembled and each system is fully tested. Final adjustments are made to ensure the machine is ready for use.

Note: Some parts are disassembled for shipping.

PRICE:

Please inquire for pricing.

OPTIONS:.

- Air conditioned cab
- Air conditioned and heated cab
- Forward and rear view camera system

SALE CONDITIONS:

PRICES.....F.O.B., TOL Incorporated

DELIVERY.....According to availability

TERMS.....20% deposit required to confirm an order.
Balance due on delivery.

PACKING:

One machine in 40’ Container

NOTES:

- As our policy is of continuous improvement, we reserve the right to change specifications and design without prior notice.