

HDR1100-4PU DUAL BOOM HEDGER TOPPER
SPECIFICATION SHEET

SPECIFICATIONS:

- CUTTING STAR DIAMETER.....11' (336 CM)**
- MINIMUM HEDGING WIDTH.....2' (61 CM)**
- MAXIMUM HEDGING WIDTH.....13'5" (409 CM)**
- MAXIMUM HEDGING HEIGHT (AT 2' HEDGING WIDTH).....23'4" (710 CM)**
- MAXIMUM FLAT TOPPING HEIGHT.20' (610 CM)**
- TRANSPORT HEIGHT (WITH BLADES INSTALLED).....11'4" (344 CM)**
- MACHINE WEIGHT.....21,400 LBS (9700 KG)**
- SAW BLADES6 - 24" DIAMETER, PROPRIETARY SAW BLADES**

SELF PROPELLED POWER UNIT:

Includes the following components:

- ITL** heavy duty front and rear axles
- JOHN DEERE** 4045T Tier 3, 99HP, turbo charged diesel engine
- JOHN DEERE / FUNK** pump drive
- JOHN DEERE / FUNK** 2-speed transmission
 - Operation mode: 0 – 5 MPH
 - Transport mode: 0 – 12 MPH
- EATON** hydrostatic drive system
- Heavy Duty front and rear rims and tires
- Rear 16.9 x 34 – 18 ply forestry tire
- Front 14.9 x 24 – 18 ply forestry tire

HYDRAULIC SYSTEM:

- Saw blade rotation circuit – **COMMERCIAL** gear type pump.
- Cross rotation circuit – **EATON** variable displacement, piston pump with 2000 series **CHARLYNN** motor.
- Control circuit – Gear type pump operating:
 - Tower lift cylinder
 - Cutting arm width cylinders
 - Cutting arm angle cylinders
 - Engine hood lift cylinder
- Hydrostatic drive circuit – **EATON** pump and motor
- Cooling package fan circuit – gear type pump

OPERATOR CAB:

The large, heavy duty, flat-deck operator's cab is mounted as a separate unit on rubber mounts to reduce noise, vibration and heat. Pressure gauges mounted on the control panel allow the operator to continually monitor the machine load. The front windows of the cab are made of tempered glass providing unobstructed vision and safety. The side windows are covered with a laser cut metal screens for ventilation (Air conditioned cabs include tempered glass on the side windows).

COOLING SYSTEM :

A self-cleaning cooling system mounted at the rear of the machine contains three radiators for the following:

- Engine coolant
- Hydraulic oil
- AC condenser

A maintenance free, automatic dust vacuum system removes and discharges debris before it gets to the radiators to ensure constant operation under normal working temperature.

SAFETY:

In the design, components selection, and manufacturing, as well as in the servicing and operating instructions, much thought has been given to providing a machine with high productivity, low maintenance, long life, and above all operator safety.

LITERATURE:

Each unit is supplied with full documentation for all systems. This includes a “General Safety and Operations Manual” and a “Specifications and Spare Parts Manual”.

FINISH:

- Machine parts are sand blasted, primed and painted.
- Machine bolts are zinc plated, grade 5.
- Saw blade propelling and rotation parts (pulleys, shafts, washers, etc.) are zinc plated.
- The machine is assembled and each system is fully tested. Final adjustments are made to ensure the machine is ready or use.

Note: Some parts are disassembled for packing.

PRICE:

Please inquire for pricing.

OPTIONS:

- 140 HP Tier 3 John Deere diesel engine
- Air conditioned cab
- Air conditioned and heated cab
- Front axle stabilizer
- Forward and rear view camera system

SALE CONDITIONS

- | | |
|--|---|
| <input type="checkbox"/> PRICES | F.O.B., TOL Incorporated |
| <input type="checkbox"/> DELIVERY | According to availability |
| <input type="checkbox"/> TERMS | 20% deposit required to confirm an order.
Balance due on delivery. |

PACKING:

One machine in a 20' Container.

NOTES:

- As our policy is of continuous improvement, we reserve the right to change specifications and design without prior notice.