

# **HDR1100N-H**

## **Narrow Dual Boom Topper Hedger**



**Hedging as Narrow as 2 feet!**



**Dual Boom Flat Topping**



### **HDR1100N-H Narrow - Dual Boom - Topper Hedger**

The HDR1100N-H was designed to meet the growing demand for a dual boom, topper hedger able to hedge as narrow as 2 feet. The unique design of the machine allows each boom to be moved independently of each other making the HDR1100N-H one of our most versatile and productive machines to date.

Cutting Pass	11' 3"
Min Hedging Width	2'
Max Flat Topping Height	20'
Max Hedging Height	24'

\*When hedging at 2' wide

**Note:** All dimensions are rounded

The HDR1100N-H is mounted on our own power unit that features:

- John Deere 6068H Tier 3 155HP Diesel Engine
- Hydrostatic Transmission
- Heavy Duty Axles & Rims, 18 Ply Tires

The unique design of the HDR1100N-H allows each boom to be moved independently of each other. This allows the machine to perform mechanical pruning operations that simply were not possible in the past. For example, flat topping one side while hedging on the other.



The front suspension combined with the "walking beam" rear axle of the HDR1100N-H provides a stable ride over berms when cross hedging. The narrow power unit and cutting arms provide for efficient hedging in the tightest planted orchards

### **Compact design for easy transport**



The machines pictured in this brochure are intended to illustrate the general appearance and features of these products. They are equipped as specified by a particular customer and may or may not show items that are optional or recommended. Specifications, illustrations, and descriptive materials herein were accurate as known at the time this publication was approved for printing. We reserve the right to discontinue models or options at any time or to change specifications and materials, equipment and design without notice and without incurring obligation.