

TH1100CT-H SELF PROPELLED - HIGH REACH - COMBINATION TOPPER HEDGER
SPECIFICATION SHEET

SPECIFICATIONS:

- ❑ **CUTTING STAR DIAMETER**.....11’3” (343 CM)
- ❑ **MAXIMUM FLAT TOPPING HEIGHT**.....21’2” (645 CM)
- ❑ **REACH FROM MACHINE CENTER (RIGHT SIDE)**.....12’7” (383 CM)
- ❑ **REACH FROM MACHINE CENTER (LEFT SIDE)**.....1’3” (38 CM)
- ❑ **MAXIMUM HEDGING HEIGHT**.34’ (1,036 CM)
- ❑ **TRANSPORT HEIGHT (WITH BLADES INSTALLED)**.....11’ (335 CM)
- ❑ **MACHINE WEIGHT**.....21,600 LBS (9800 KG)
- ❑ **SAW BLADES**5 - 24" DIAMETER, PROPRIETARY SAW BLADES

SELF PROPELLED POWER UNIT:

Includes the following components:

- ❑ **ITL** heavy duty front and rear axles
- ❑ **JOHN DEERE** 4045T Tier 3, 99HP, turbo charged diesel engine
- ❑ **JOHN DEERE / FUNK** pump drive
- ❑ **JOHN DEERE / FUNK** 2-speed transmission
 - ❑ Operation mode: 0 – 5 MPH
 - ❑ Transport mode: 0 – 12 MPH
- ❑ **EATON** hydrostatic drive system
- ❑ Heavy Duty front and rear rims and tires
- ❑ Rear 16.9 x 34 – 18 ply forestry tire
- ❑ Front 14.9 x 24 – 18 ply forestry tire

HYDRAULIC SYSTEM:

- ❑ Saw blade rotation circuit – **COMMERCIAL** gear type pump.
- ❑ Cross rotation circuit – **EATON** variable displacement, piston pump with 2000 series **CHARLYNN** motor
- ❑ Control circuit – Gear type pump operating:
 - ❑ Tower lift cylinder
 - ❑ Secondary tower lift cylinder
 - ❑ Horizontal to vertical cylinder
 - ❑ Engine hood lift cylinder
 - ❑ Cutting star swing cylinder
- ❑ Hydrostatic drive circuit – **EATON** pump and motor

OPERATOR CAB:

The large, heavy duty, flat-deck operator’s cab is mounted as a separate unit on rubber mounts to reduce noise, vibration and heat. Pressure gauges mounted on the control panel allow the operator to continually monitor the machine load. The front windows of the cab are made of tempered glass providing unobstructed vision and safety. The side windows are covered with laser cut metal screens for ventilation (air conditioned cabs include tempered glass on the side windows).

COOLING SYSTEM :

A self-cleaning cooling system mounted at the rear of the machine contains three radiators for the following:

- Engine coolant
- Hydraulic oil
- AC condenser

A maintenance free, automatic dust vacuum system removes and discharges debris before it gets to the radiators to ensure constant operation under normal working temperature.

SAFETY:

In the design, components selection, and manufacturing, as well as in the servicing and operating instructions, much thought has been given to providing a machine with high productivity, low maintenance, long life, and above all operator safety.

LITERATURE:

Each unit is supplied with full documentation for all systems. This includes a "General Safety and Operations Manual" and a "Specifications and Spare Parts Manual".

FINISH:

- Machine parts are sand blasted, primed and painted.
- Machine bolts are zinc plated, grade 5.
- Saw blade propelling and rotation parts (pulleys, shafts, washers, etc.) are zinc plated.
- The machine is assembled and each system is fully tested. Final adjustments are made to ensure the machine is ready for use.

Note: Some parts are disassembled for packing.

PRICE:

Please inquire for pricing.

OPTIONS:

- 140 HP Tier 3 John Deere diesel engine
- Air conditioned cab
- Air conditioned and heated cab
- Forward and rear view camera system

SALE CONDITIONS

- | | |
|--|---|
| <input type="checkbox"/> PRICES | F.O.B., TOL Incorporated |
| <input type="checkbox"/> DELIVERY | According to availability |
| <input type="checkbox"/> TERMS | 20% deposit required to confirm an order.
Balance due on delivery. |

PACKING:

One machine in a 20' Container.

NOTES:

- As our policy is of continuous improvement, we reserve the right to change specifications and design without prior notice.