

TH2600 Dual Arm Topper Hedger





TH2600 Dual Arm Topper Hedger

The TH2600 Topper Hedger was designed to address the need for a high reaching, dual arm topper hedger. This model is well suited to the modern hedge row style plantings becoming more common in nut orchards.

The unique design of the machine allows single pass flat topping of most trees, as well as the ability to hedge and angle top in a single pass.

Cutting Pass:	25' 2"
Max Flat Topping Height	24' 5"
Max Hedging Height	48' 2"
Max Topping Height at 30 degrees	45' 9"
Max Reach From Center	23' 11" (Right Side)

Note: All dimensions are rounded.

The TH2600 is mounted on our own power unit that features:

- John Deere 6068H Diesel Engine
- Hydrostatic Transmission
- Heavy Duty Axles, Rims, Tires
- Self Cleaning Cooling System
- Optional Air Conditioned Cab



Hedge and angle top in one pass



Compact design for easy transportation



The machines pictured in this brochure are intended to illustrate the general appearance and features of these products. They are equipped as specified by a particular customer and may or may not show items that are optional or recommended. Specifications, illustrations, and descriptive materials herein were accurate as known at the time this publication was approved for printing. We reserve the right to discontinue models or options at any time or to change specifications and materials, equipment and design without notice and without incurring obligation.